

Anliker GSM 5 Star



STANDARD FEATURES

- Kidney shaped material pusher is made from antimicrobial glass fiber compound
- Cutting head is dishwasher safe
- ◆ Powerful 1/2 HP gear-driven motor
- ◆ Optimum plate speed of 336 RPMs
- Cast stainless steel construction & sealed upper housing
- ◆ Double safety interlock hopper head and food pusher
- ◆ Ergonomic 45° food hopper incline
- Removable hopper head and food pusher (no tools required)
- Discs are antimicrobial durable composite fiberglass & dishwasher safe
- Stainless steel knives are hardened, ground, leathered and hand-polished
- ♦ 47 discs are available

CAPACITY

Processes up to 600 lbs. per hour. Ideal for up to 300-400 meals.

MOTOR

1/2 HP, 115V-60HZ-1 Phase, 3 amps, automatic reset thermal overload protection.

ON/OFF LATCH (INTERLOCKS)

The hopper latch serves as the on/off switch and interlock for the hopper head. The unit will not operate with the hopper head open or unlatched.

GEAR DRIVE

Sealed planetary gear transmission with permanent grease lubrication. Output 336 RPMs.

DESIGN

Ergonomic 45° incline for convenient feeding, cutting and ejection of food. Separate food hopper permits continuous cutting of long products. The food pusher

IOB	ITEM #	QTY #	

MODEL NUMBER

☐ GSM 5 Star

enables even pressure to be applied when cutting food. The hopper head, food pusher and cutting discs are easily removable, without the use of tools, for quick cleaning.

UNIT COMPARISONS

	GSM 4	GSM 5 Star	GSM XL
HP	1/2	1/2	1
RPMs	336	336	280
Upper Housing	Cast Aluminum	Stainless Steel	Cast Aluminum
Blades Available	42	47	40
Antimicrobial Protection Pusher		✓	1
Antimicrobial Protection Blades	1	1	

DIMENSIONS

- ◆ Foot Print = 9.84" x 12.4"
- ◆ Overall Length = 19.06"
- ◆ Overall Width = 10.83"
- ◆ Overall Height = 21.26"
- ◆ Kidney Shaped Hopper = 5.67" x 2.4"
- Brunoises/Gaufrettes Hopper = 1.85"
- ♦ Freight Class: 85
- Net Weight: 48.28 lbs.
- Shipping Weight: 56.22 lbs.
- ◆ Shipping Dimensions: 29.92"W x 14.57"D x 16.93"H

CORD AND PLUG

Attached six-foot flexible 3-wire cord and plug fits a grounded receptacle.

CONSTRUCTION

The housing, removable hinged hopper head, food hoppers, removable food pusher and ejector plate are made of polished cast stainless steel.

Cutting Discs: There are 47 cutting discs available. The discs are antimicrobial durable composite fiberglass. The knives are hardened, ground, leathered and hand-polished to a razor sharp edge for precision cutting and long life.

WARRANTY

Two years parts and labor.

SPEC T-2



300 S. 84th Avenue Wausau, WI 54401 Phone: 800-544-3057 Fax: 715-842-3125

PIPER CHEF SYSTEM

Slicing

inches

mm

Anliker GSM 5 Star



	F1-5	1/32	1
	F2-5	5/64	2
	G3-5	1/8	3
	G4-5	5/32	4
	G6-5	15/64	6
	G8-5	5/16	8
A Par	G10-5	3/8	10
5	G12-5	15/32	12
	SU5-5*	3/16	5
5	SU7-5*	9/32	7
	TO-5	3/16	5



Julienne	inches	mm
S1.5-5	1/16	1.5
S2-5	5/64	2
S3-5	1/8 x 5/64	3 x 2
PA4K-5	5/32	4
PA5K-5	3/16 x 5/32 5 x 4	5



French Fry	inches	mm
BT6-5	15/64	6
BT7-5	9/32	7
BT8-5	5/16	8
BT10-5	3/8	10





Shredding	inches	mm
11-5	5/64	2
9-5	3/32	2.5
7-5	1/8	3
4-5	5/32	4
3-5	3/16	5
1-5	9/32	7
0-5	23/64	9
00-5	7/16	11
23-5	3/32	2.5



Dicing	inches	mm
W6-5	1/4 x 1/4 x 5/16	6 x 6 x 8
W8-5	5/16	8
W10-5	3/8	10
W14-5	9/16	14
W20-5 *	25/64 x 25/64 x 25/64	20 x 20 x 20



23

Shaving	inches	mm
HS-5	1/64	.5
•		





*Soft Only Products

Brunoise	inches	mm
BR3-5	1/8	3
BR4-5	5/32	4
BR5-5	7/32	5



HS

SM	

Grating	
14-5	fine cut (parmesan and romano cheese powder)

Sickle Disc	inches	mm
SM1.5-5	1/16	1.5
SM2.5-5	3/32	2.5
SM3.5-5	9/94	3.5
SM4.5-5	11/64	4.5
SM5.5-5	7/32	5.5
SM6.5-5	1/4	6.5



W6

PG4



Gaufrette	inches	mm
PG4-5	5/32	4
PG6-5	15/64	6

Option	Describuon
SCV-1	Vertical disc storage case (1 disc) *Will not hold cubing or dicing discs
SCH-3	Vertical disc storage case (3 discs)
SCH-4	Vertical disc storage case (4 discs)
SCV-7/3	Vertical disc storage rack (3 discs)
WR3	Three peg wall rack

T-2 SPEC

PIPER PRODUCTS BUILT TO LAST www.piperonline.net

300 S. 84th Avenue Wausau, WI 54401 Phone: 800-544-3057 Fax: 715-842-3125

LIMITED WARRANTY: PIPER PRODUCTS warrants to the original purchaser parts and labor for a period of twelve (12) months from the date of purchase. See manufacturer's complete warranty for details.

It is our policy to build equipment which is design certified by companies that have been accredited at the Federal Level by the Occupational Safety and Health Agency (OSHA) and ANSI as a National Recognized Testing Laboratory. These companies include CSA International, Underwriters Laboratories, and the National Sanitation Foundation. However, a continuing program of product improvement makes it necessary to submit new models to the agencies as they are developed. Consequently, all models may use they appropriate labels at all times. developed. Consequently, all models may not bear the appropriate labels at all times.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Information is not for design purposes.